

# HSF 0

## Super Cut Advanced Compound

### Description :

Formulated without silicone and using a new technology of micro abrasives particles derived from nanotechnology, this HSF 0 Super Cut Advanced Compound gives quicker and more efficient job than the old generation of compound for removing permanently coarser scratches on old or new paint finishes.

This new generation of HSF (Hologram Swirl Free) lubricant frictionless compound, specially formulated, uses a new low VOC lubricant process to be used for several polishing applications; prevents haze and swirl marks on dark colours. Produces a super wet look finish on all polished surface without using water, reducing splashing and clean up time.


### Advantages :

- Excellent to remove scratches and 1000 grit sand paper swirls.
- Ideal for new generation paint systems, cured paints and older finishes.
- Safe for body shops, silicone free, does not hide scratches.
- Ideal for blending-in, matching of gloss levels and general paint restoration.
- Reduces polish time by 50%.
- Formulated with lubricant that extends life of pad and assists in a smoother and easier running of the pad.

### Instructions :

- 1- Apply a good quantity of HSF 0 on the surface you wish to treat with the 100% wool buffing pad (Velcro grip # 4038). Spread the product on approximately 60 sq cm (2 sq ft.) to avoid splashing before using the polisher.
- 2- Use a variable speed polisher (from 1200 to 1500 RPM). Let it work slowly until a shiny oily effect appears, while applying medium pressure, if needed, wipe with a micro fibre cloth.
- 3- Repeat step one (1) with HSF 1 to eliminated swirl marks left by HSF 0.
- 4- To remove deep scratches on the surface such as (pig tail), use faster speed ( 2500 RPM) and more pressure on the polisher, which may cause swirl marks and holograms. The use of HSF 2 (no. 672-032) with a black finishing foam (Velcro # 4237) will remove swirl marks and holograms.
- 5- For professional results, use HSF 3 Advanced finishing glaze (no. 673-032) and Liquid polymers wax (no. 601-032) is recommended.

Regular cleaning of the pad with help of pad washer (no. S2000) is highly recommended to avoid swirl marks and holograms.



n° 670-032 6 X 1lt Box / n° 670-01 4 X 3.78lt Box